

MULTI-PURPOSE MARINE HOSE

MULTI-PURPOSE
AUTOMOTIVE,
MARINE, COOLANT,
AND FUEL HOSE.
INDUSTRY STANDARD
WHERE FLEXIBILITY,
REINFORCEMENT,
AND KINK RESISTANCE
ARE REQUIRED.



NOMINAL SPECIFICATIONS				
PART NO.	I.D. (in)	W.P. (psi)	MBR (in)	WEIGHT (lbs/ft)
16791005025	1/2	50	2 1/2	0.32
16791006225	5/8	50	2 1/2	0.36
16791007560	3/4	50	2 1/2	0.48
16791008760	7/8	50	3	0.55
16791010060	1	50	3	0.61
16791012560	1 1/4	50	3	0.72
16791013760	1 3/8	50	4	0.79
16791015060	1 1/2	50	4	0.84
16791016260	1 5/8	50	5	0.90
16791017560	1 3/4	50	5	0.96
16791018760	1 7/8	50	5	1.02
16791020060	2	50	6	1.07
16791021260	2 1/8	50	6	1.13
16791022560	2 1/4	50	7	1.18
16791023760	2 3/8	50	7	1.19
16791025060	2 1/2	50	8	1.23
16791026260	2 5/8	50	9	1.28
16791027560	2 3/4	50	10	1.34
16791028760	2 7/8	50	11	1.40
16791030060	3	50	13	1.51
16791031260	3 1/8	50	15	1.57
16791032560	3 1/4	50	15 1/2	1.63
16791035060	3 1/2	50	15 1/2	1.75
16791040060	4	50	16	1.98
16791045060	4 1/2	50	18	2.21

TUBE: Black Nitrile (NBR).

COVER: Black Chloroprene Rubber (CR) with yellow lay-line.

REINFORCEMENT: Polyester fabric plies with wire helix.

SERVICE TEMPERATURE RANGE: -30°F to +212°F
(-35°C to +100°C)

FEATURES:

- Tube is petroleum and heat resistant.
- Flame and oil resistant cover.
- Working pressure is 25% rated burst pressure.
- Meets or exceeds requirements for
 - Vital water applications: SAE 1942-1
 - Marine exhaust: SAE J2006 R2
 - Fuel fill hose: SAE J1527 Type A2, ISO 7840, USCG, NMMA, ABYC
- Extremely versatile with applications including cabin heating, bilge pump intake, discharge and ventilation, internal water systems including toilet, bath, galleys and drains.