

EXTRA FLEXIBLE NITRILE FOOD
150 PSI SUCTION & DISCHARGE HOSE

RECOMMENDED FOR OILY & NON-OILY FOOD & BEVERAGE TRANSFER APPLICATIONS THAT DEMAND BOTH FLEXIBILITY AND RUGGEDNESS. THE FOOD GRADE NITRILE TUBE IS ODORLESS AND TASTELESS FOR THOSE OILY TRANSFER APPLICATIONS. THIS ULTRA SMOOTH MICROBE RESISTANT TUBE IS BUILT OF SPECIAL STAINLESS STEEL MANDRELS FOR CLEANLINESS.



Construction:

Tube: FDA white nitrile
Reinforcement: Multiple plies of polyester tire cord with helix wire
Cover: Grey PVC nitrile corrugated
Length: 100 ft.
Temperature Range -40°F (-40°C) to +210°F (+99°C)
Cleaning in Place to 248°F (+120°C)
Not for continuous steam service

NOTE: Meets FDA, USDA & 3A sanitary standards Authorized #1376.

| Part No. | I.D. | O.D. | Plies | WP psi | MBR | WT LBS/FT |
|-----------------|------|------|-------|-----------|------|--------------|
| 6314WT-01500-00 | 1½ | 2.05 | 2 | 150 | 2" | 1.04 |
| 6314WT-02000-00 | 2 | 2.55 | 2 | 150 | 3" | 1.34 |
| 6314WT-02500-00 | 2½ | 3.05 | 2 | 150 | 4" | 10.57 |
| 6314WT-03000-00 | 3 | 3.75 | 2 | 150 | 5" | 2.78 |
| 6314WT-04000-00 | 4 | 4.76 | 2 | 150 | 6.5" | 3.82 |