



ULTRA-HIGH PRESSURE SMOOTHBORE TEFLON HOSE

THE PINNACLE IN
TRANSFER HOSE FOR HIGH-
PRESSURE SITUATIONS. THIS
STOUT TEFLON (PTFE)
LINED HOSE COMBINES
DURABILITY AND LONGEVITY
WITH FLEXIBILITY, MAKING
FOR A SMART, COST
EFFECTIVE INVESTMENT.



HOSE CONSTRUCTION: Conductive Polytetrafluoroethylene (PTFE) liner

BRAID MAKEUP: Grade 304 stainless steel

BRIAD CONSTRUCTION: Unique weight & bulk reducing non-spiral wrap design

TEMPERATURE RANGE: -65°F to 400°F (-54°C to 204°C).

WORKING PRESSURE: Maximum 5000psi at 70°F

FEATURES

- Phthalate-free
- Non-leaching
- Ideal for auto sealants, compressed natural gas, industrial gasses, reaction injection molding.

PART NUMBER	SIZE (in)	I.D. (in)	O.D. (in)	MAX WP (psi)	BURST PSI (psi)	MIN BEND RADIUS (in)	WEIGHT (lbs/ft)
SBHP-04	0.2500	0.222	0.375	5000	15000	1.5	0.10
SBHP-06	0.3750	0.308	0.475	5000	15000	2.5	0.16
SBHP-08	0.5000	0.403	0.600	5000	15000	2.87	0.23
SBHP-10	0.6250	0.505	0.715	5000	15000	3.25	0.32
SBHP-12	0.7500	0.630	0.970	5000	15000	3.87	0.66
SBHP-16	1.000	0.867	1.250	5000	15000	5.00	1.02

All pressures and vacuum ratings were calculated at 70°F

TEFLON