



STAINLESS STEEL BRAIDED SMOOTH BORE TEFLON HOSE

PRIZED FOR ITS EASE OF
CLEANING, HIGH DEGREE
OF FLEXIBILITY AND
UNINTERRUPTED FLOW,
OUR SMOOTH BORE HOSE
IS IDEAL FOR THOSE
APPLICATIONS WHERE
THE UNIQUE QUALITY OF
PTFE IS REQUIRED.



NON-CONDUCTIVE



CONDUCTIVE

HOSE MAKEUP: FDA approved PTFE tube
BRAID MAKEUP: Grade 304 Stainless Steel
CONSTRUCTION: Natural and Anti-Static Smooth Bore
TEMPERATURE RANGE:
Continuous Service: -65°F to 400°F (-54°C to 204°C)
Intermittent Service: -100°F to 500°F (-73°C to 260°C)

- FEATURES**
- High flexibility
 - Vertically extruded innercore
 - -4 through -10 are rated for full vacuum
 - SAE 100R14 compliant

PART NUMBER		I.D.	O.D.	MAX WP	BURST PSI	MINIMUM	WEIGHT
(Non-Conductive)	(Conductive)	(in)	(in)	(psi)	(psi)	BEND (in)	(lbs/ft)
SB-03*	SBB-03*	0.1390	0.258	3000	12,000	2.00	0.05
SB-04	SBB-04*	0.1880	0.301	3000	12,000	2.00	0.07
SB-05	SBB-05*	0.2500	0.365	3000	12,000	3.00	0.10
SB-06	SBB-06*	0.3130	0.433	2500	10,000	4.00	0.11
SB-08	SBB-08*	0.4100	0.524	2000	8000	5.20	0.13
SB-10	SBB-10*	0.5040	0.633	1500	6000	6.50	0.15
SB-12	SBB-12*	0.6360	0.763	1200	4800	7.75	0.17
SB-16	SBB-16*	0.8750	1.01	800	3200	9.00	0.27
SB-20*	SBB-20*	1.125	1.315	800	3200	16.00	0.54
*MADE TO ORDER - All pressures and vacuum ratings were calculated at 70°F							