

ALARM BOOSTER™ FIRE ENGINE HOSE

THE ALARM BOOSTER™ HOSE IS A HIGH QUALITY, ALL-PURPOSE FIRE ENGINE BOOSTER HOSE BUILT TO TAKE RUGGED TREATMENT. THE NBR/PVC COVER RESISTS ABRASION WHILE PROVIDING A SMOOTH SURFACE FOR EASY HANDLING, MAKING IT THE DRIVERS CHOICE. ENGINEERED TO BE DIMENSIONALLY STABLE AND NOT FLATTEN OR CRUSH REELS. DESIGNED TO PROVIDE A CONSTANT 800 PSI WORKING PRESSURE.



Cover Color:	Red
Oil Resistance:	Medium, high
Construction:	
Tube:	NBR/PVC, RMA Class A
Cover:	NBR/PVC, RMA Class A, 1-1/2" I.D. EPDM
Reinforcement:	2-spiral aramid yarn
Temperature Range:	-20°F to +190°F, 1-1/2" I.D. -40°F to +190°F -29°C to +88°C, 1-1/2" I.D. -40°C to +88°C
Packaging:	Reels, coupled lengths available on a make-to-order basis

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22212482662	3/4	19.05	1.19	30.16	2	800	5.51	4.50	114.30	0.41	0.61
22214642662	1	25.40	1.50	38.10	2	800	5.51	7.00	177.80	0.51	0.76
00142524301	1-1/2	38.10	2.00	50.80	4	250	1.72	10.50	266.70	0.71	1.06

* Reattachable chrome-plated aluminum NST spanner hole couplings available to fit 3/4" and 1" I.D.