




# FLEX-LOC™ PUSH-ON

EXTREMELY FLEXIBLE WITH 250 PSI WORKING PRESSURE, FLEX-LOC IS DESIGNED FOR SAFE AND RELIABLE PERFORMANCE IN DEMANDING AND HARSH CONDITIONS. ALLOWING FOR PUSH-ON FITTINGS TO BE INSERTED EASILY AND QUICKLY WITHOUT SPECIAL CRIMPING TOOLS. IDEAL FOR INDUSTRIAL AND WAREHOUSE APPLICATIONS WHERE A CONVENIENT PUSH-ON FITTING COULD BE USED.



<p><b>RESISTANCE</b></p> <div style="display: flex; justify-content: space-around;">    </div> <p>Oil    Ozone    Weathering</p> <p><b>BRANDING:</b> Size WP Flex-Loc Made In USA Month/Day/Year Time Stamp</p> <p><b>COVER COLOR:</b> Black, Blue, Gray, Red, Green, Yellow</p> <ul style="list-style-type: none"> <li>• Allows for Color Coding</li> </ul> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Not recommended for fuel line hose applications or for impulse applications.</p> </div>	<p><b>CONSTRUCTION</b></p> <p><b>TUBE:</b> Nitrile, ARPM - Class A</p> <p><b>COVER:</b> Nitrile Blend, ARPM - Class A</p> <p><b>REINFORCEMENT:</b> 4-Spiral Polyester Yarn</p> <ul style="list-style-type: none"> <li>• Easier to Route Assemblies</li> <li>• Easier to Coil and Handle</li> <li>• Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque</li> <li>• Grips the Fitting from the Inside</li> </ul> <p><b>TEMPERATURE RANGE:</b> -20°F to +180°F, -29°C to +82°C</p>	<p><b>PACKAGING:</b> Reels 700 ft. or 250 ft.</p> <ul style="list-style-type: none"> <li>• Over 80% One Piece Reels</li> <li>• Less Scrap</li> <li>• Most Footage per Reel vs. Competition</li> </ul> <p><b>PRESSURELESS CURE SYSTEM</b></p> <ul style="list-style-type: none"> <li>• Minimal Cast (Natural Curvature of the Hose)</li> <li>• Extends the Life of the Rubber Compounds</li> </ul> <p><b>AIR MANDREL MANUFACTURING PROCESS</b></p> <ul style="list-style-type: none"> <li>• No Internal Contamination of the Inside Diameter Due to the Lubricant</li> <li>• Eliminates the Need for Customers to Flush the Hose</li> </ul> <p><b>PUSH-ON HOSE CONSTRUCTION</b></p> <ul style="list-style-type: none"> <li>• Allows the Fittings to be Inserted into Place Easily</li> <li>• No Special Crimping Equipment Required</li> </ul>
---	--	---

Product Number		Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
700 ft. Reels	250 ft. Reels	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
<b>BLACK</b>												
00338404300	00338404398	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338406300	00338406398	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338408300	00338408398	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
00338410300	00338410398	⅝	15.88	0.91	23.02	2	250	1.72	3.75	95.25	0.22	0.33
00338412300	00338412398	¾	19.05	1.03	26.19	2	250	1.72	4.50	114.30	0.25	0.37
<b>BLUE</b>												
00338504300	00338504398	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338506300	00338506398	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338508300	00338508398	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
<b>GRAY</b>												
00338604300	00338604398▲	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338606300	00338606398▲	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338608300	00338608398▲	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
<b>RED</b>												
00338704300	00338704398▲	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338706300	00338706398	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338708300	00338708398▲	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
<b>GREEN</b>												
00338804300	00338804398▲	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338806300	00338806398▲	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338808300	00338808398▲	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
<b>YELLOW</b>												
00338904300	00338904398	¼	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338906300	00338906398▲	⅜	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338908300	00338908398▲	½	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24

AIR - MULTIPURPOSE