

GREEN GP / OXYGEN

THE GREEN GP/OXYGEN HOSE IS DESIGNED TO HANDLE THE HARSH, ABUSIVE CONDITIONS FOUND IN STEEL PRODUCING AND OIL REFINERY ENVIRONMENTS. THE GREEN COVER FOLLOWS THE COLOR CODING FOR OXYGEN IN MILLS.



***NOT RECOMMENDED FOR FUEL OR AIR BREATHING APPLICATIONS.**

RESISTANCE



BRANDING: Size 300# W.P. -GP/OXYGEN
MADE IN USA Date and Time Stamp

COVER COLOR: Green
• Allows for Color Coding

CONSTRUCTION

TUBE: Nitrile Blend, ARPM - Class B

COVER: Nitrile Blend, ARPM - Class B
• Abrasion Resistant
• Weather Resistant
• Ozone Resistant

REINFORCEMENT: 4-Spiral Polyester Yarn
• Provides a Working Pressure to 300 psi
• More Flexible than Braid Reinforced Hose
• Easier to Route Assemblies
• Easier to Coil and Handle
• Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque

TEMPERATURE RANGE: -20°F to +180°F, -29°C to +82°C

PACKAGING:

- 700 ft. Reels
- Over 80% One Piece Reels
- Less Scrap
- Most Footage per Reel vs. Competition

PRESSURELESS CURE SYSTEM

- Minimal Cast (Natural Curvature of the Hose)
- Extends the Life of the Rubber Compounds

AIR MANDREL MANUFACTURING PROCESS

- No Internal Contamination of the Inside Diameter Due to the Lubricant
- Eliminates the Need for Customers to Flush the Hose

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius	
	Reels (ft.)	inches	mm	inches	mm		psi	Mpa	inches	mm
00336606400	700	3/8	9.53	0.71	22.23	4	300	2.07	2.25	57.15
00336608400	700	1/2	12.70	0.94	23.81	4	300	2.07	3.00	76.20
00336612400	700	3/4	19.05	1.16	29.37	4	300	2.07	4.50	114.30