



# PUMPFLEX® 1 - SOFTWALL HOSE

PUMPFLEX® 1 IS DESIGNED FOR CURB PUMP APPLICATIONS AT SERVICE STATIONS AND CONVENIENCE STORES AND IS THE LONGEST LASTING AUTOMOTIVE REFUELING HOSE IN USE AT SERVICE STATIONS TODAY. THE DURABLE CONSTRUCTION OF THIS HOSE RESISTS DETERIORATION FROM FUEL, OZONE, SUNLIGHT AND CRACKING AROUND/BEHIND THE NOZZLE END COUPLING.



#### RESISTANCE



**BRANDING:** Thermoid Size Pumpflex I Gasoline Hose UL Listed 97MO Made In USA Month/Year

**COVER COLOR:** Black

#### CONSTRUCTION

**TUBE:** Nitrile Blend, ARPM - Class A

- Oil Resistant
- Gasoline Resistant
- Kerosene Resistant
- Diesel Resistant
- Bio-Diesel Fuel Resistant

**COVER:** Thermalon™, U/L Approved, Class B

- Medium Oil Resistant
- Ozone and Sunlight Resistant

**REINFORCEMENT:** 2-Spiral Polyester Cord with Static Wire (Softwall)

- Provides a Working Pressure to 150-200 psi Depending on the I.D.

**TEMPERATURE RANGE:** -40°F to +180°F, -40°C to +82°C

**PACKAGING:** Reels or Coupled Lengths – See Table Below  
• Meets Industry Standards

**WARNING:** Do not use reuseable couplings with this product.

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22462401662	500	5/8	15.88	1.03	26.19	2	200	1.38	3.75	95.25	0.27	0.40
22462481662	500	3/4	19.05	1.13	28.58	2	200	1.38	4.50	114.30	0.32	0.48
22464641662	450	1	25.40	1.50	38.10	4	150	1.03	7.00	177.80	0.62	0.92