




PUMPFLEX® MARINA SOFTWALL

DESIGNED TO HANDLE AND PERFORM IN SEVERE WEATHER CONDITIONS, THIS DURABLE SOFTWALL GAS HOSE IS IDEAL FOR ROUGH DECK OR DOCK USE. THE OIL AND WEATHER RESISTANT UL-APPROVED COVER IS GREEN COLOR-CODED TO DESIGNATE MARINA USE. **NOTE: CAN BE USED FOR ALL TYPES OF GASOLINE, OIL AND OTHER PETROLEUM PRODUCTS.**



RESISTANCE			CONSTRUCTION				TEMPERATURE RANGE: -40°F to +180°F, -40°C to +82°C					
			TUBE: Nitrile Blend, ARPM - Class A				PACKAGING: Reels					
Gasoline	Oil	Weathering	<ul style="list-style-type: none"> • Oil Resistant • Gasoline Resistant 				<ul style="list-style-type: none"> • Color Codes this Hose for Marina Use 					
BRANDING: Thermoid Size Pumpflex Marina Hose UL Listed 97MO Made In USA Month/Year			COVER: Chlorinated Polyethylene, ARPM - Class A				STATIC WIRE, ALL SIZES					
COVER COLOR: Green			<ul style="list-style-type: none"> • Medium Oil Resistant • Weather Resistant 				<ul style="list-style-type: none"> • Enables User to Ground the Hose, Dissipating a Build Up of Electricity 					
REINFORCEMENT: 4-Spiral Polyester Yarn with Static Wire (Softwall)			<ul style="list-style-type: none"> • Provides a Working Pressure to 150 to 200 psi 									
Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22463484662	500	¾	19.05	1.13	28.58	4	200	1.38	4.50	114.30	0.32	0.48
22464644662	450	1	25.40	1.50	38.10	4	150	1.03	7.00	177.80	0.62	0.92