

PLIOVIC®

A LIGHTWEIGHT, ECONOMICAL GENERAL PURPOSE HOSE FOR CARRYING AIR, WATER AND MANY SPRAY SOLUTIONS. PLIOVIC® IS SUITABLE FOR A WIDE RANGE OF INDUSTRIES, FROM CONSTRUCTION SITES TO AGRICULTURAL HAND SPRAYERS AND MANY MORE MULTIPURPOSE APPLICATIONS.



CONSTRUCTION TUBE: Black Pliovic®, RMA Class B (Medium Oil Resistance)

COVER: Pliovic®, smooth finish, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -10 °F to 158 °F (-23 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Pliovic® GS 3/8" ID (9.5 mm) 250 psi WP. Made in USA. Continental Contitech

SKU	ID (in)	NOMINAL OD (in)	COLOR	MAX W.P. (psi)	WEIGHT (lbs)
21218410	3/8	0.660	RED	300	0.13
21218594	1/2	0.810	RED	300	0.17
21218595	3/4	1.110	RED	300	0.28
21218596	1	1.380	RED	250	0.37
21218418	1/4	0.500	BLUE	300	0.08
21218520	3/8	0.660	BLUE	300	0.13
21218521	1/2	0.810	BLUE	300	0.17
21218522	3/4	1.110	BLUE	300	0.28
21218524	1	1.380	BLUE	250	0.37
21218411	3/8	0.660	BLACK	300	0.08
21218413	1/2	0.810	BLACK	300	0.13
21218412	3/4	1.110	BLACK	300	0.17
21218415	1	1.380	BLACK	250	0.37

AIR - MULTIPURPOSE