

# T614AA SERIES

## 150 PSI HOT TAR & ASPHALT S&D

DESIGNED FOR THE  
TRANSFER OF TAR,  
ASPHALT, HOT OILS AND  
OTHER HIGH  
TEMPERATURE  
PETROLEUM-BASED  
PRODUCTS.

NOT FOR USE WITH  
BIOFUELS



### General Applications:

Hot tar and asphalt suction and discharge service.

### Construction:

**Tube:** Black NBR – hot tar and asphalt resistant.

**Reinforcement:** High tensile textile cords with steel helix wire.

**Cover:** Black CSM – abrasion, ozone and hot tar resistant.

### Working Pressure:

10 Bar (150 PSI)

### Service Temperature Range:

-4°F (-20°C) to +356°F (+180°C)

### Branding:

ALFAGOMMA – ITALY T614 10 BAR (150 PSI)  
HOT TAR AND ASPHALT (on red stripe)

## Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Wall Thickness (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
T614AA200	2	51	2.72	69	9	150	30	10	100	1.64
T614AA300	3	76	3.78	96	10	150	27	15	100	2.69
T614AA400	4	102	4.80	122	10	150	27	20	100	3.57